

WARNING

Hazard Statements: Harmful if swallowed. Causes skin irritation. Causes eye irritation. Harmful to aquatic life with long-lasting effects.



PRECAUTIONARY STATEMENTS

Prevention: Keep container tightly closed. Keep only in original container. Keep cool. Avoid breathing mist, vapors or spray. Do not get in eyes, on skin, or on clothing. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use in a well-ventilated area. Avoid release to the environment. Wear protective gloves and eye protection. Read Safety Data Sheet carefully before handling.

Response/First Aid:

IF SWALLOWED: Call a doctor if you feel unwell. Rinse Mouth. Do NOT induce vomiting.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
IF ON SKIN: Wash with plenty of water and soap. Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
If any irritation persists, get immediate medical attention.

In case of fire: Use water spray, alcohol-resistant foam, carbon dioxide (CO₂) or dry chemical to extinguish.

Storage: Store in a well-ventilated place. Protect from sunlight. Keep from freezing. Store at temperatures 45-90 °F.

Disposal: Dispose of contents and container to an approved waste disposal plant in accordance with applicable local, state, federal and international regulations.

FLEX-SHEEN

FLOOR FINISH & SEALER #9664

ACABADO Y SELLADOR DE PISOS

For VCT, Vinyl & Terrazzo Floors

18% solids (unless marked otherwise)

25% solids _____% solids

Net 5 Gallons (18.9 Liters)



www.ArcotManufacturing.com
2950 Mowery Road, Houston, Texas 77045 (713) 413-9700

High gloss, self-shining, with or without high speed buffing / Alto lustre, con o sin brulimiento

Durable and repairable / Durable y reparable

Resistant to black marks / Resistente a marcas de tacon negro

Application

General Instructions: Mix well before use. Clean floor with Arcot EASY MOP. Strip old finish with Arcot EASY STRIP or Arcot LIFT-OFF. Apply thin coats of FLEX-SHEEN with a clean rayon mop. Allow sufficient drying time between coats.

For a floor with old finish, clean floor and let dry. Then, apply two or more thin coats of FLEX-SHEEN.

To a thoroughly stripped, cleaned and dried floor, apply five or more thin coats of FLEX-SHEEN.

Store at room temperature. Keep from freezing.

Aplicacion

Instrucciones Generales: Mezcle bien antes de usar. Limpie pisos con Arcot EASY MOP. Pele acabado viejo con Arcot EASY STRIP o Arcot LIFT-OFF. Aplique capas delgadas de FLEX-SHEEN con un trapeador de rayon. Permita tiempo suficiente para secarse entre capas.

Para un piso con acabado viejo, limpie el suelo y deje secar. Despues, aplique dos o más capas delgadas de FLEX-SHEEN.

Para pisos pelados, despues de pelar, limpiar, enjuagar y secar completamente, aplique cinco o más capas delgadas de FLEX-SHEEN.

Almacene en la temperatura ambiente. Evite de congelar.

For Commercial & Industrial Use Only
Keep Out Of Reach Of Children
Solamente Para El Uso Comercial E Industrial
Mantengalo Fuera Del Alcance De Los Niños